E 11 E V E N

GIA-6WR



DESCRIPTION

A compact 6" loudspeaker for hospitality use, hotels, restaurants, lobbies, bars, and ambient background music. Weatherized Version.

KEY FEATURES

- 2-WAY Passive Point Source
- 1" compression driver with polymer diaphragm
- Threaded fixing points for wall mounts
- Ultra-Compact passive two-way system
- Vertical and horizontal orientation
- Weatherized

APPLICATIONS

- Nightclubs
- VIP Rooms
- Bar & Lounges
- Live Music Venues

SPECIFICATIONS

Performance Frequency Range (+/-3dB	93 Hz – 20 kHz
Horizontal Coverage (-6 dB)	80°
Vertical Coverage (-6 dB)	50°
Nominal Impedance	8 ohms
Power Handling RMS	150W
Sensitivity 1W @ 1m	94 dB SPL
Maximum Peak SPL at 1m	114 dB Peak
Recommended Amplifier	EP-60004
Recommended Processor	BSS & Q-Sys
Connectors	
Audio Input Connector	1 x Neutrik NL4
Audio Output Connector	1 x Neutrik NL4
Enclosure	
Enclosure Construction	Premium Birch Plywood
Enclosure Geometry	Trapezoidal
Color	Black, White or RAL
Finish	Marine Grade Paint
Dimensions (H x W x D)	(13.4" x 8.3" x 8.3")
NI - 4 NA/- Color	4711 (7.71.)

17 lbs. (7.7 kg)



Net Weight

E 11 E V E N

Components

L/F Driver	GIA6-6WOOFER
Diaphragm	GIA6-6DIA
H/F Driver	GIA6-6HORN
Shipping	
Shipping Weight	19 lbs. (8.6 kg)
Accessories	
GIA8-HMBRK	GIA6 Horizontal Bracket
GIA6-VMBRK	GIA6 Vertical Bracket

DIMENSIONS







