

GIA-8



APPLICATIONS

- Nightclubs
- VIP Rooms
- Bar & Lounges
- Live Music Venues

SPECIFICATIONS

Performance

Frequency Range (+/-3dB) 85 Hz – 20 kHz

Horizontal Coverage (-6 dB) 80°

Vertical Coverage (-6 dB) 50°

Nominal Impedance 8 ohms

Power Handling RMS 180W

Sensitivity 1W @ 1m 93 dB SPL

Maximum Peak SPL at 1m 114 dB Peak

Recommended Amplifier EP-60004

Recommended Processor BSS & Q-Sys

Connectors

Audio Input Connector 1 x Neutrik NL4

Audio Output Connector 1 x Neutrik NL4

Enclosure

Enclosure Construction Premium Birch Plywood

Enclosure Geometry Trapezoidal

Color Black, White or RAL

Finish ISO-flex Paint

Dimensions (H x W x D) (16.5" x 11.4" x 10.2")

Net Weight 24.5 lbs. (11.1 kg)

DESCRIPTION

A compact 8" loudspeaker for hospitality use, hotels, restaurants, lobbies, bars, and ambient background music, or lounge where music is played louder than ambient.

KEY FEATURES

- 2-WAY Passive Point Source
- 1" compression driver with polymer diaphragm
- Threaded fixing points for wall mounts
- Ultra-Compact passive two-way system
- Vertical and horizontal orientation

E11EVEN

///SOUND

Components

L/F Driver	GIA8-8WOOFER
Diaphragm	GIA8-8DIA
H/F Driver	GIA8-8HORN

Shipping

Shipping Weight	27.3 lbs. (12.4 kg)
-----------------	---------------------

Accessories

GIA8-HMBRK	GIA8 Horizontal Bracket
GIA6-VMBRK	GIA8 Vertical Bracket

DIMENSIONS

