

## MIA-L3-14



### APPLICATIONS

- VIP Rooms
- Bar & Lounges
- Live Music Venues

### SPECIFICATIONS

#### Performance

Frequency Range (+/-3dB) 100 Hz – 20 kHz

Horizontal Coverage (-6 dB) 120°

Vertical Coverage (-6 dB) 45°

Nominal Impedance 4 ohms

Power Handling RMS 440W

Sensitivity 1W @ 1m 98 dB SPL

Maximum Peak SPL at 1m 127 dB Peak

Recommended Amplifier EP-60004

Recommended Processor BSS & Q-Sys

#### Connectors

Audio Input Connector 1 x Neutrik NL4

Audio Output Connector 1 x Neutrik NL4

#### Enclosure

Enclosure Construction Premium Birch Plywood

Enclosure Geometry Column

Color Black, White or RAL

Finish ISO-flex Paint

Dimensions (H x W x D) (48.1" x 3.8" x 4.1")

Net Weight 26 lbs. (11.8 kg)

### DESCRIPTION

A unique high powered column speaker where aesthetics is extremely important to designers and architects. Slim and sleek look with hidden small rear vertical bracket. Loudspeaker must be accompanied by GIA210S or GIA310S subwoofer using BSS or Q-SYS signal processing.

### KEY FEATURES

- 2-WAY Passive Point Source
- Ultra-Compact passive two-way system
- High Power Column Speaker

# E11EVEN

**SOUND**

## Components

L/F Driver MIAL3-14-3WOOFER

H/F Driver MIAL3-15-3DIA

## Shipping

Shipping Weight 28 lbs. (12.7 kg)

## Accessories

MIAL4-VMBRK Vertical Bracket

## DIMENSIONS

