

GIA-5.5



DESCRIPTION

A unique coaxial speaker cube shaped, for restaurants, lounges, ambient background music and music played slightly higher than ambient, appropriate for applications where you want the customers to enjoy the music, not be overwhelmed, and still be able to talk at normal conversation level. Must be accompanied by GIA210S using BSS or QSYS signal processing.

KEY FEATURES

- 2-WAY Passive Coaxial Enclosure
- Threaded fixing points for wall mounts
- Ultra-Compact passive two-way system
- Mounting Bracket included

APPLICATIONS

- VIP Rooms
- Bar & Lounges

SPECIFICATIONS

Performance

Frequency Range (+/-3dB)	95 Hz – 20 kHz
Nominal directivity (-6 dB)	110° axisymmetric
Nominal Impedance	8 ohms
Power Handling RMS	150W
Sensitivity 1W @ 1m	94 dB SPL
Maximum Peak SPL at 1m	121 dB Peak
Recommended Amplifier	EP-60004
Recommended Processor	BSS & Q-Sys

Connectors

Audio Input Connector	1 x Neutrik NL4
Audio Output Connector	1 x Neutrik NL4

Enclosure

Enclosure Construction	Premium Birch Plywood
Enclosure Geometry	Trapezoidal
Color	Black, White or RAL
Finish	ISO-flex Paint
Dimensions (H x W x D)	(6.5" x 6.5" x 6.5")
Net Weight	7.7 lbs. (3.5 kg)

E11EVEN

SOUND

Components

L/F Driver	GIA5.5-WOOFER
H/F Driver	GIA5.5-DIA

Shipping

Shipping Weight	8 lbs. (3.6 kg)
-----------------	-----------------

Accessories

U Bracket Included

DIMENSIONS

