

GIA-6



APPLICATIONS

- Nightclubs
- VIP Rooms
- Bar & Lounges
- Live Music Venues

SPECIFICATIONS

Performance

Frequency Range (+/-3dB)	93 Hz – 20 kHz
--------------------------	----------------

Horizontal Coverage (-6 dB)	80°
-----------------------------	-----

Vertical Coverage (-6 dB)	50°
---------------------------	-----

Nominal Impedance	8 ohms
-------------------	--------

Power Handling RMS	150W
--------------------	------

Sensitivity 1W @ 1m	94 dB SPL
---------------------	-----------

Maximum Peak SPL at 1m	114 dB Peak
------------------------	-------------

Recommended Amplifier	EP-60004
-----------------------	----------

Recommended Processor	BSS & Q-Sys
-----------------------	-------------

Connectors

Audio Input Connector	1 x Neutrik NL4
-----------------------	-----------------

Audio Output Connector	1 x Neutrik NL4
------------------------	-----------------

Enclosure

Enclosure Construction	Premium Birch Plywood
------------------------	-----------------------

Enclosure Geometry	Trapezoidal
--------------------	-------------

Color	Black, White or RAL
-------	---------------------

Finish	ISO-flex Paint
--------	----------------

Dimensions (H x W x D)	(13.4" x 8.3" x 8.3")
------------------------	-----------------------

Net Weight	17 lbs. (7.7 kg)
------------	------------------

DESCRIPTION

A compact 6" loudspeaker for hospitality use, hotels, restaurants, lobbies, bars, and ambient background music.

KEY FEATURES

- 2-WAY Passive Point Source
- 1" compression driver with polymer diaphragm
- Threaded fixing points for wall mounts
- Ultra-Compact passive two-way system
- Vertical and horizontal orientation

E11EVEN

SOUND

Components

L/F Driver	GIA6-6WOOFER
Diaphragm	GIA6-6DIA
H/F Driver	GIA6-6HORN

Shipping

Shipping Weight	19 lbs. (8.6 kg)
-----------------	------------------

Accessories

GIA8-HMBRK	GIA6 Horizontal Bracket
GIA6-VMBRK	GIA6 Vertical Bracket

DIMENSIONS

