

MIA-15



APPLICATIONS

- Nightclubs
- VIP Rooms
- Bar & Lounges
- Live Music Venues

SPECIFICATIONS

Performance

Frequency Range (+/-3dB)	70 Hz – 20 kHz
Horizontal Coverage (-6 dB)	80° (Rotatable)
Vertical Coverage (-6 dB)	50°
Nominal Impedance	8 ohms
Power Handling RMS	600W
Sensitivity 1W @ 1m	99 dB SPL
Maximum Peak SPL at 1m	125 to 131 dB Peak
Recommended Amplifier	EP-13004
Recommended Processor	BSS & Q-Sys

Connectors

Audio Input Connector	1 x Neutrik NL4
Audio Output Connector	1 x Neutrik NL4

Enclosure

Enclosure Construction	Premium Birch Plywood
Enclosure Geometry	Trapezoidal
Color	Black, White or RAL
Finish	ISO-flex Paint
Dimensions (H x W x D)	(27.2" x 16.8" x 16.5")
Net Weight	52.9 lbs. (24 kg)

DESCRIPTION

MIA15 fulfils the requirement for a medium size system that can deliver high sound levels and should be accompanied by the MIA18 or MIA218 subwoofer. Featuring a powerful 15" (380mm)/3" (75mm) voice coil LF drive unit, and a 1" (25mm) exit HF compression driver with a 1.75" (44mm) polyimide diaphragm for extended high frequency response.

KEY FEATURES

- 2-WAY Passive Point Source
- 1" compression driver with polymer diaphragm
- Threaded fixing points for wall mounts

E11EVEN

SOUND

Components

L/F Driver MIA15-10DR

H/F Driver MIA15-H/FDR

Shipping

Shipping Weight 55.2 lbs. (25 kg)

Accessories

Eyebolts

DIMENSIONS

