

MIA-215



DESCRIPTION

Two 15" woofers within an innovative enclosure, the MIA215 boasts a hybrid construction that brings together the advantages of bass reflex and horn loaded subwoofer design - high efficiency, a superb range and the ability to reach extraordinarily low frequencies. The unique design engages the subwoofer's entire front baffle to enhance the acoustic field while reducing friction and minimizing losses. The result is an impressively efficient signal to noise ratio, faithful low-end reproduction and excellent dynamic coverage.

KEY FEATURES

- Dual-driver, direct radiating subwoofer
- Omnidirectional

APPLICATIONS

- Nightclubs
- VIP Rooms
- Bar & Lounges
- Live Music Venues

SPECIFICATIONS

Performance

Frequency Range (+/-3dB)	35 Hz – 200 Hz
Coverage	Omnidirectional
Nominal Impedance	4 ohms
Power Handling RMS	2000W
Sensitivity 1W @ 1m	102 dB SPL
Maximum Peak SPL at 1m	133 dB
Recommended Amplifier	EP-34004
Recommended Processor	BSS & Q-Sys

Connectors

Audio Input Connector	1 x Neutrik NL4
Audio Output Connector	1 x Neutrik NL4

Enclosure

Enclosure Construction	Primium Birch Plywood
Color	Black, White or RAL
Finish	ISO-flex Paint
Dimensions (H x W x D)	(27.8" x 17.56" x 31.5")
Net Weight	85 lbs. (38.7 kg)

E11EVEN

SOUND

Components

L/F Driver

MIA215S-15DR

Shipping

Shipping Weight

87 lbs. (39.5 kg)

DIMENSIONS

