

E11EVEN

SOUND

GIA-C6



APPLICATIONS

- Boardrooms & Corporate Offices
- Shopping Malls, Retail Spaces & Showrooms
- Restaurants, Bars & Lounges
- Galleries & Museums
- Casinos, Convention Centers & Hotels
- Houses of Worship
- Educational Facilities

SPECIFICATIONS

Performance

| | |
|--------------------------|-----------------|
| Frequency Range (+/-3dB) | 65 Hz – 20 kHz |
| Coverage (-6 dB) | 140° |
| Nominal Impedance | 8 ohms |
| Power Handling RMS | 90W@8Ω/60W@100V |
| Sensitivity 1W @ 1m | 89 dB SPL |
| Maximum Peak SPL at 1m | 108 dB Peak |
| Recommended Amplifier | EP-60004 |
| Recommended Processor | BSS & Q-Sys |

Connectors

| | |
|-----------------|--------------------|
| Audio Connector | Four Pin Euroblock |
|-----------------|--------------------|

Enclosure

| | |
|-------------------------------|---------------------|
| Dimensions (Diameter x Depth) | 9.37" x 8.86" |
| Cut Out Diameter | 8.07" |
| With Grille Diameter | 9.37" |
| Color | Black, White |
| Net Weight | 6.97 lbs. (3.16 kg) |

DESCRIPTION

Experience exceptional performance and seamless design with the E11EVEN Sound GIA-C6 in-ceiling speaker. Featuring a bezel-less magnetic grille and an optional square adapter, it blends effortlessly into any environment. The high-excursion 6" woofer and pivoting tweeter deliver precise, full-range sound for immersive audio coverage. A sealed metal enclosure with cable clamping, a removable Euroblock connector, and a seismic attachment ensures secure installation and long-term reliability. UL 1480 and UL 2043 certifications provide added assurance of safety and compliance in commercial settings.

KEY FEATURES

- Bezel-less design for clean and minimalistic aesthetic
- Full-fidelity transformer for uncompromised tonality
- Optional black grilles in round or square
- Magnetic grille retention for fast installation and removal
- One-step simplified painting process
- Front-mounted finger-adjustable selector tap
- Exceptional off-axis response

E11EVEN

SOUND

Enclosure

| | |
|---------------------------|-------------------------------------|
| Knockouts | One, side mounted .75" |
| Safety Agency | UL 1480, UL 2043, NFPA 90A, NFPA 70 |
| Maximum Ceiling Thickness | 1.732" (44mm) |
| Suspension Points | One, on top surface |

Shipping

| | |
|-----------------|---------------------------|
| Shipping Weight | 35.94 lbs. (16.3 kg) 4pcs |
|-----------------|---------------------------|

DIMENSIONS

